



hp-FEM with deal.II, 3.1.2006

The hp-method within the deal.II framework

Oliver Kayser-Herold

Institut für Wissenschaftliches Rechnen
Technische Universität Braunschweig



The hp-method within the deal.II framework

1. Concept
2. Internals
3. Example (step-21)
4. Missing functions
5. hp-FEM for continuous elements
6. Summary and Outlook



1. Concept


- Standard DoFHandler: Same FiniteElement on all cells
- hpDoFHandler: Different FiniteElement on all cells!
- DoFHandler as template parameter for Accessor classes.
- Instead of an unique FiniteElement, a collection of FiniteElements (FECollection)
- Collection of Mappings (MappingCollection) and Quadrature rules (QCollection).





2. Internals

hpLevelObject:

Line



DoFindizes





3. Example (step-21)

Class definition

```
template <int dim>
class DGMethod
{
[...]
```

FECollection<dim>	fe_collection;
hpDoFHandler<dim>	dof_handler;

```

    std::vector<Quadrature<dim> *> quad;
    QCollection<dim> *quadrature;
    std::vector<Quadrature<dim-1> *> face_quad;
    QCollection<dim-1> *face_quadrature;

[...]
```

const DGTransportEquation<dim>	dg;
--------------------------------	-----

```
};
```



3. Example (step-21)

Constructor

```
template <int dim>
DGMethod<dim>::DGMethod () [...]
{
    quadrature = new QCollection<dim> ();
    Quadrature<dim> *quad_temp;

    const unsigned int hp_degree = 5;
    for (unsigned int i = 0; i < hp_degree; ++i)
    {
        elm_no = fe_collection.add_fe (FE_DGQ<dim> (i+1));

        quad_temp = new QGauss<dim> (i+2);
        quad.push_back (quad_temp);
        quadrature->add_quadrature (*quad_temp);
    }
}
```



3. Example (step-21)

Cell assembly

```
typename SelectFEValues<hpDoFHandler<dim> >::FEValues fe_v_x (  
    mapping, fe_collection, *quadrature, update_flags);  
    [...]  
const unsigned int max_dofs_per_cell =  
    fe_collection.max_dofs_per_cell ();  
FullMatrix<double> u_v_matrix (max_dofs_per_cell,  
                                max_dofs_per_cell);  
fe_v_x.reinit (cell);  
dg.assemble_cell_term(fe_v_x.get_present_fe_values (),  
    u_v_matrix, cell_vector);
```



3. Example (step-21)

Face assembly

```
typename SelectFEValues<hpDoFHandler<dim> >::FEFaceValues
    fe_v_face_x (mapping, fe_collection,
                 *face_quadrature, face_update_flags);

// Determine higher active_fe_index of both cells
const unsigned int use_fe_index =
    neighbor_child->active_fe_index () > cell->active_fe_index () ?
    neighbor_child->active_fe_index () : cell->active_fe_index ();

fe_v_subface_x.reinit (cell, face_no, subface_no, use_fe_index);
fe_v_face_neighbor_x.reinit (neighbor_child, neighbor2,
                             use_fe_index);
```





3. Example (step-21)

hp-Refinement

```
GridRefinement::refine_and_coarsen_fixed_number (  
    triangulation, gradient_indicator, 0.3, 0.1);  
  
                                                    // Simple heuristic hp-Refinement.  
cell = dof_handler.begin_active ();  
for (; cell!=endc; ++cell)  
    if (!cell->refine_flag_set ())  
        cell->set_active_fe_index (cell->active_fe_index () + 1);  
  
triangulation.execute_coarsening_and_refinement ();
```




3. Results (step-21) I






3. Results (step-21) II






3. Results (step-21) III






3. Results (step-21) IV





3. Results (step-21) V





4. Missing functions

- Several functions in DoFTools are not yet implemented for the hpDoFHandler
- Usually some changes are required to cope with a different number of `dofs_per_cell`.




5. DoFHandler algorithm

- Distribute DoFs on vertices (all D)
- Distribute DoFs on lines (all D)
- Distribute DoFs on quads (2D, 3D)
- Distribute DoFs on hexes (3D)

For DG the lower geometric entities are not equipped with DoFs, while they are for continuous elements!



5. hp-FEM for continuous elements



Key problem: **No** active_fe_index on lower geometric entities (lines in 2D, lines and quads in 3D)!



5. Proposal 1

Make the `active_fe_index` available on lower geometric entities:

```
class DoFObjectAccessor : public DoFAccessor<dim, DH>,
    public TriaObjectAccessor<celldim,dim>
```

Old:

```
typedef DH<dim> AccessorData;
```

New:

```
typedef typename std::pair<DH<dim> const *,
    unsigned int> AccessorData;
```



5. Proposal 1

Advantages:

- `active_fe_index` might be useful
- Distribution of DoFs similar to implemented procedure

Disadvantages:

- Several parts of the `deal.II` lib will have to be modified




5. Proposal 2

- Change algorithm which distributes DoFs
- Instead of treating the geometric entities sequential, the DoFs will be distributed cell wise.
- Not completely clear if it is possible



5. Data structure





6. Summary and Outlook

- hp method works for DG
- In some cases functions from DoFTools might not yet be available
- Adapting the methods to work with the hpDoFHandler pathes the way for future extensions (hybrid meshes)
- Some work has to be done for cont. elements
- hpMGDoFHandler ??